

30UC3020

LOAD BREAK SWITCH SIRCO UL, 3X200A IN PAINTED STEEL ENCLOS. RED HANDLE

Strong points

- High switching performance, easy wiring
- Robust and ergonomic handle

General characteristics

- Several enclosures: polycarbonate, polyester, stainless steel, painted steel.
- Full range of NEMA ratings: 1, 3R, 12, 4, 4X.
- Reliable switching technology.
- Robust and ergonomic padlockable handle.
- Large range of accessories.

Compliance with standards

- UL98, Guide WHTY File E201138
- CSA 22.2#4, Class 4652-04 File 703166
- UL 508A

Link to the reference

<https://www.socomec.us/en->

[us/reference/30UC3020](https://www.socomec.us/en-us/reference/30UC3020)

Enclosed SIRCO are non-fusible disconnect switches provided with an enclosure. They operate the disconnection upstream from the motor and isolate a load for maintenance operations.

----- System -----	
Fill rate E-Order Common	67
Fill rate E-Order Selection	25
Standards	
Conformity to standards	UL
Technical Characteristics	
Number of poles	3
Rated current [A]	200
Type	Steel enclosure LBS
Logistics	
GTIN/EAN	3596033022807
Customs number	8537109899
Price unit	PC
Weight of the packing unit	35
Product Details	
Effective date	2019-01-01
Country of origin	MX
Discount Policy	1CM20
Discount Policy Label	ENCLOSED LBS
Length of the product unit	0.61
Width of the product unit	0.406
Depth of the product unit	0.152
Classification	
UNSPSC	39122205
ETIM Class	EC000216
IGCC	5176