

30UC3060

LOAD BREAK SWITCH SIRCO UL, 3X600A IN PAINTED STEEL ENCLOS. RED HANDLE

Strong points

- High switching performance, easy wiring
- Robust and ergonomic handle

General characteristics

- Several enclosures: polycarbonate, polyester, stainless steel, painted steel.
- Full range of NEMA ratings: 1, 3R, 12, 4, 4X.
- Reliable switching technology.
- Robust and ergonomic padlockable handle.
- Large range of accessories.

Compliance with standards

- UL98, Guide WHTY File E201138
- CSA 22.2#4, Class 4652-04 File 703166
- UL 508A

Link to the reference

<https://www.socomec.us/en->

[us/reference/30UC3060](https://www.socomec.us/en-us/reference/30UC3060)

Enclosed SIRCO are non-fusible disconnect switches provided with an enclosure. They operate the disconnection upstream from the motor and isolate a load for maintenance operations.

| ----- System ----- | |
|-----------------------------|---------------------|
| Fill rate E-Order Common | 67 |
| Fill rate E-Order Selection | 25 |
| Standards | |
| Conformity to standards | UL |
| Technical Characteristics | |
| Number of poles | 3 |
| Rated current [A] | 600 |
| Type | Steel enclosure LBS |
| Logistics | |
| GTIN/EAN | 3596033022821 |
| Customs number | 8537109899 |
| Price unit | PC |
| Weight of the packing unit | 85 |
| Product Details | |
| Effective date | 2019-01-01 |
| Country of origin | MX |
| Discount Policy | 1CM20 |
| Discount Policy Label | ENCLOSED LBS |
| Length of the product unit | 1.219 |
| Width of the product unit | 0.762 |
| Depth of the product unit | 0.254 |
| Classification | |
| UNSPSC | 39122205 |
| ETIM Class | EC000216 |
| IGCC | 5176 |