

## 30UC3120

# LOAD BREAK SWITCH SIRCO UL, 3X1200A IN PAINTED STEEL ENCL. RED HANDLE.

### Strong points

- High switching performance, easy wiring
- Robust and ergonomic handle

### General characteristics

- Several enclosures: polycarbonate, polyester, stainless steel, painted steel.
- Full range of NEMA ratings: 1, 3R, 12, 4, 4X.
- Reliable switching technology.
- Robust and ergonomic padlockable handle.
- Large range of accessories.

### Compliance with standards

- UL98, Guide WHTY File E201138
- CSA 22.2#4, Class 4652-04 File 703166
- UL 508A

### Link to the reference



<https://www.socomec.us/en-us/reference/30UC3120>

Enclosed SIRCO are non-fusible disconnect switches provided with an enclosure. They operate the disconnection upstream from the motor and isolate a load for maintenance operations.

### Certificates and Declaration

Proposition 65 California	WARNING This product can expose you to chemicals including Styrene, which is known to the State of California to cause cancer. For more information go to: <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
---------------------------	---

### Standards

Conformity to standards	UL
-------------------------	----

### Technical Characteristics

Height [mm]	1524
Width [mm]	914
Depth [mm]	254
Number of poles	3
Rated current [A]	1200
Type	Steel enclosure LBS

### ETIM - Mechanical characteristics

Width [mm]	914
Height [mm]	1524
Depth [mm]	254

### Logistics

GTIN/EAN	3596033022845
Customs number	8537109899
Price unit	PC
Weight of the packing unit [kg]	132

### Product Details

Effective date	2019-01-01
Offer Life Cycle Code	40
Country of origin	MX

### Classification

UNSPSC	39122205
ETIM Class	EC000216
IGCC	5176