

**41503021**

## Manually operated transfer switch body SIRCOVER UL1008 3P 200A

### Strong points

- Stable positions
- Compact design
- On-load switching
- Reliability

### General characteristics

Three stable positions, not affected by voltage drops or vibrations.  
 Back to back switching design offering an extremely compact solution.  
 Make and break under load conditions to provide safety of person and equipment.

### Compliance with standards

UL 1008, Guide WPYV File E317092  
 UL 98, Guide WHTY File E201138  
 CSA 22.2#4, Class 4651-02, File 112964

### Link to the reference

<https://www.socomec.us/en-us/reference/41503021>

SIRCOVER are heavy-duty manual transfer switches. They ensure switching transfer of sources or transfer of two low voltage circuits on load as well as their safe disconnection.

These extremely durable switches are tested and approved for use in the most demanding applications, such as resistive load or total system applications.

### ----- System -----

Fill rate E-Order Common	33
Fill rate E-Order Selection	62

### Standards

Conformity to standards	UL
-------------------------	----

### Technical Characteristics

Number of poles	3
Rated current [A]	200

### ETIM - Electrical characteristics

Max. rated operation voltage Ue AC [V]	600
Rated operating voltage [V]	240..600
Rated permanent current Iu [A]	200
Number of poles	3

### ETIM - Mechanical characteristics

Suitable for floor mounting	No
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	No
Suitable for intermediate mounting	Yes
Colour control element	Black
Degree of protection (IP), front side	IP20

### ETIM - Technical features

Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	No
Version as reversing switch	Yes
Number of switches	2
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No
Device construction	Built-in device fixed built-in technique
Type of control element	Door coupling rotary drive
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection

### Logistics

GTIN/EAN	3596031982004
Customs number	8536508090
Price unit	PC
Weight of the packing unit	5.38
Length of the packing unit	0.266
Width of the packing unit	0.378

Depth of the packing unit	0.381
<b>Product Details</b>	
Effective date	2009-11-10
Country of origin	FR
Discount Policy	1CH37
Discount Policy Label	SIRCOVER UL
Weight	5.38
<b>Classification</b>	
UNSPSC	39122205
ETIM Class	EC000216
IGCC	5177