

45162520

Insulated copper braid X=200 mm L=220mm 250A



Strong points

- Easy setup
- Wide range of applications
- Compatibility

General characteristics

Tin-plated contact surface available  
Compact and flexible for ease of installation  
Adapted to various types of connection terminals  
Compatibility with any devices on the market

Compliance with standards

IEC  
UL

Link to the reference

<https://www.socomec.us/en-us/reference/45162520>

SOCOMECS insulated flat copper braids are mainly utilized for providing the power connections between series of distribution busbars and the upstream devices within an electrical panel.  
Their flexibility is especially adapted to achieve complex and customized connections in cases where minimum space is available.

----- System -----	
Fill rate E-Order Common	100
Fill rate E-Order Selection	100
Standards	
Conformity to standards	IEC UL
Technical Characteristics	
Height	20
Length	220
Model	Insulated Copper Braid
Thickness	3
ETIM - Electrical characteristics	
Rated current In [A]	250
ETIM - Mechanical characteristics	
Length [mm]	220
Width [mm]	20
Height [mm]	3
Surface protection	Other
ETIM - Technical features	
Model	Other
Flexible	Yes
Logistics	
GTIN/EAN	3596032741815
Customs number	8544499590
Price unit	PC
Weight of the packing unit	0.1
Length of the packing unit	0.025
Width of the packing unit	0.002
Depth of the packing unit	0.025
Product Details	
Effective date	2013-03-27
Country of origin	FR
Discount Policy	1CK10
Discount Policy Label	COPPER BAR
Length of the product unit	0.005
Width of the product unit	0.02
Depth of the product unit	0.22
Weight	0.1
Classification	
UNSPSC	26121634
ETIM Class	EC001522
IGCC	1786