

45181304

Insulated flexible copper bar 4x13x0.5 L=2000mm



SOCOMEC insulated flexible copper bars are mainly utilized for providing the power connections between series of distribution busbars and the upstream devices within an electrical panel.

The insulated layered copper allows the flexible copper bar to be easily formed to provide a customized solution.

Strong points

- Easy setup
- Increased safety without crimped connections
- Conductor

General characteristics

High level of flexibility enabling easy manipulation
Tin-plated contact surface available Increased safety by the elimination of crimped connections
Available on request: specific lengths, halogen-free

Compliance with standards

UL67, Guide QEUY2 File E495516

Link to the reference

Certificates and Declaration	
Conformity to standard #1	UL 67 and UL891 Guide QUEY File E495516
Conformity to standard #2	CSA-22.2 No. 29 and 244
Proposition 65 California	WARNING This product can expose you to chemicals including Styrene, Formaldehyde which is known to the State of California to cause cancer. For more information go to: www.P65Warnings.ca.gov

Standards

Conformity to standards	IEC	
Certificates and Declaration - Safety		
UL file number	E495516	

Technical Characteristics	
Length of the product unit [mm]	2000
Width of the product unit [mm]	13
Depth of the product unit [mm]	0.5
Weight [kg]	0.66
Height [mm]	13
Length	2000
Model	Insulated Flexible Copper Bar
Thickness	0.5
Number of layers	4

Technical Characteristics - Environmental

Operating temperature	-4 +122°F / -20 +50°C
Storage temperature	-40 +158°F / -40 +70°C

165

Technical Characteristics - Short-circuit capacity

ETIM - Electrical characteristics	
Rated current In [A]	165

ETIM - Mechanical characteristics

Surface protection	Other
Height [mm]	0.5
Width [mm]	13
Length [mm]	2000

ETIM - Technical features

Weight of the packing unit [kg]

Model

UL General use rating [A]

Flexible	Yes
Logistics	
GTIN/EAN	3596031224555
Customs number	7409190000
Price unit	PC

Other

0.66

2025-05-11 16:05:37





Length of the packing unit [m]	0.03
Width of the packing unit [m]	0.04
Depth of the packing unit [m]	2
Product Details	
Effective date	2000-08-01
Offer Life Cycle Code	40
Country of origin	DE
Classification	
UNSPSC	26121634
ETIM Class	EC001522
IGCC	1786

2025-05-11 16:05:37