

# 48290160

# Current acquisition module DIRIS Digiware S-130, 3 current sensors, 63A



#### Strong points

- Plug & Play
- Multi-circuit
- Compact
- Accurate

#### General characteristics

Three current sensors are embedded to the DIRIS Digiware S power monitoring

The most compact power meter on the market

Provide real time physical state of protective devices (ON/OFF/TRIP) with VirtualMonitor technology Quick RJ45 connection between modules to add more metering points to the system Class 0.5 in accordance with ANSI

C12.20

## Compliance with standards

UL 61010 Guide FTRZ/PICQ File E257746 IEC 61557-12

### Link to the reference

2024-05-03 09:06:10 1/3



https://www.socomec.us/enus/reference/48290160

DIRIS Digiware S current measurement modules have 3 integrated current sensors for measuring, monitoring and analyzing power quality of electrical circuits up to 63  $_{\rm A}$ 

Positioned directly downstream protective devices, they offer new and exclusive technologies:

VirtualMonitor which gives the real time physical state of protective devices (ON/OFF/TRIP).

AutoCorrect which detects wiring errors and corrects them to guarantee consistent readings, even when no load is connected.

Adding DIRIS Digiware S modules to the bus is done simply by clicking in an RJ45 cable. This allows great flexibility to the user who wishes to add more metering points in the future.

60
UL 61010-1 Guide PICQ File E257746
CSA-C22.2 No. 61010-1
IEC 61557-12
WARNING This product can expose you to chemicals including bisphenol A (BPA), which is known to the State of California to cause birth defects or reproductive harm. For more information go to: www.P65Warnings.ca.gov
IEC UL
fety
IEC/EN 61010-1 UL 61010-1 CAN/CSA C22.2 No. 61010-1
E257746
Currentmeasurementmodulewith3integrated current sensors for DIRIS Digiware system
Metering
S-130
3
Current acquisition module with integrated current sensors
onmental
14 +131 °F / -10 +55 °C
SOCO-00006-v01.01-fr, SOCO-00006-v01.01-en
104 °F / 40 °C / 95% RH
-13 + 158 °F / -25 +70 °C
urement
Class 0.5
AC
10-63 A

2/03 2/05-03 09:06:10



	measurement: I1, I2, I3, In, ?P, ?Q, ?S, ?PF
ETIM - Electrical characteristics	
Sampling frequency [Hz]	10000
Number of current measurement inputs	3
Voltage type (supply voltage)	DC
Supply voltage DC [V]	024
Supporting protocol for IEC 61850 Ethernet	No
Supporting protocol for OPC UA PubSub	No
Supporting protocol for PROFIBUS	No
Supporting protocol for Modbus	Yes
Supporting protocol for PROFINET IO	No
Supporting protocol for other bus systems	No
With audit logging (audit log)	No
With firmware signature	Yes
With logging of security events (security event log)	Yes
With Role Based Access Control (RBAC)	No
Web server with HTTPS transfer protocol	No
ETIM - Mechanical characteristics	
Width [mm]	54
Height [mm]	28
Depth [mm]	42.5
Degree of protection (IP), front side	IP20
ETIM - Technical features	
Ampere meter	Yes
Blind power meter	Yes
With rotational speed meter	No
Frequency meter	No
Pulse counter	No
Voltmeter	No
Effective power measurement device	Yes
Remote display	No
Logistics	
GTIN/EAN	3596033020056
Customs number	9030337000
Price unit	PC
Weight of the packing unit	0.09
Length of the packing unit	0.12
Width of the packing unit	0.08
Depth of the packing unit	0.035
Product Details	
Effective date	2018-02-01
Country of origin	FR
Discount Policy	1EN20
Discount Policy Label	ELECTRONIC SENSORS
	LLLO INCINIO GLINOONO
Classification	20101000
UNSPSC	83101808
ETIM Class	EC002301
IGCC	6042

2024-05-03 09:06:10 3/3