

54100025

CONNECTOR FOR DISTRIBUTION BLOCK UNIPOLAIRE 250 A

Allows use of standard solid, stranded and fine wire strands with use of compression sleeve.
From 90 A to 255 A.



Strong points

- IP20 finger safe protection
- Wide range
- Easy integration
- UL & IEC range

Compliance with standards

- UL 1953, Guide QPQS, File E500778
- UL 1059, CSA-C22.2 No. 128, Guide XCFR, File E500524
- IEC 61439-1
- IEC 60947-7-1

Link to the reference

----- System -----

Fill rate E-Order Common	33
Fill rate E-Order Selection	100

Standards

Conformity to standards	IEC
-------------------------	-----

Technical Characteristics

Rated current [A]	250
-------------------	-----

ETIM - Technical features

Type of accessory/spare part	Connector
Accessory	Yes
Spare part	No

Logistics

GTIN/EAN	3596031630202
Customs number	8536901000
Price unit	PC
Weight of the packing unit	0.05
Length of the packing unit	0.065
Width of the packing unit	0.005
Depth of the packing unit	0.025

Product Details

Effective date	2002-07-05
Country of origin	DE
Discount Policy	1CK30
Discount Policy Label	CONNECTION DEVICE

Classification

UNSPSC	39121421
ETIM Class	EC002498
IGCC	4586

<https://www.socomec.us/en-us/reference/54100025>