

57035006

**RM cylind. fuse holder without sign. aux. cont.-100A-4P-NFC-
Fuse 22x58**

Strong points

- Improved safety
- High breaking capacity
- Format and specific accessories

General characteristics

Accepts Class Midget and CC fuses
Very high short circuit protection, up to 200 kAIC
Enhanced safety with touch safe design
Smallest footprint on the market
Label holder for a fast identification

Compliance with standards

UL 4248-1,
CSA C22.2, class 4248-1,
Guide IZLT,
File E307648,

IEC 60269-2,-1

Link to the reference



<https://www.socomec.us/en-us/reference/57035006>

RM and RMS are modular fuse holders for class midget and CC fuses. They provide safety disconnection and protection against overcurrent and short circuits in any low-voltage electrical circuit.

- RM: Non-signalling fuse holders for fuses without strikers.
- RMS: Fuse holders with pre-break auxiliary contact, position, and blown indication.

Certificates and Declaration

Conformity to standard #1	UL 4248-1,Guide IZLT File E307648
Conformity to standard #2	CSA-C22.2 No 4248-1
Conformity to standard #3	IEC 60269-2-1
Conformity to standard #4	ML E307648
Proposition 65 California	WARNING This product can expose you to chemicals including Styrene, which is known to the State of California to cause cancer. For more information go to: www.P65Warnings.ca.gov

Standards

Conformity to standards	IEC UL
-------------------------	------------

Certificates and Declaration - Safety

Safety standards	IP20
UL file number	E307648

Technical Characteristics

Height [mm]	126.5
Width [mm]	143
Depth [mm]	76.5
Weight [kg]	0.709
Fuse melting indicator	no
Fuse size	22x58
Number of poles	4
Rated current [A]	100
Size	RM/RMS 100

Technical Characteristics - Connection terminals

Max. connection section / AWG	1 AWG (Solid), 2 AWG (Stranded)
Min. connection section / AWG	16 AWG

Technical Characteristics - Environmental

Operating temperature	-4 ... +122°F / -20 ... +50°C
Storage temperature	-40 ... +158°F / -40 ... +70°C

Technical Characteristics - Mechanical

Operating torque [lbs.in/Nm]	35/4
------------------------------	------

Technical Characteristics - Short-circuit capacity

Max fuse rating [A]	125
Operation voltage 2 P - 3/4 P	750
Short circuit rating at 600 VAC [kA]	100
Type of fuse	Midget/ Ferrule
UL General use rating [A]	100

ETIM - Electrical characteristics

Nominal voltage [V]	690
---------------------	-----

Number of poles	4
Concurrently switching neutral conductor	No
ETIM - Mechanical characteristics	
Mounting method	DIN rail
For fuse size	22x58 mm
Width in number of modular spacings	1
Built-in depth [mm]	49.5
Degree of protection (IP)	IP2X
Logistics	
GTIN/EAN	3596032687113
Customs number	8536109090
Price unit	PC
Weight of the packing unit [kg]	0.682
Length of the packing unit [m]	0.152
Width of the packing unit [m]	0.084
Depth of the packing unit [m]	0.135
Product Details	
Effective date	2012-06-25
Offer Life Cycle Code	40
Country of origin	ES
Classification	
UNSPSC	39121624
ETIM Class	EC002705
IGCC	4974