

**57050013**

## Modular fuse holder 3P 600V with LED



### Strong points

- Improved safety
- High breaking capacity
- Specific format and accessories
- Label holder

### General characteristics

Accepts Class CC fuses  
Very high short circuit protection, up to 200 kAIC  
Enhanced safety with touch safe design  
Smallest footprint on the market  
Label holder for a fast identification

### Compliance with standards

UL 4248-4, Guide IZLT File E307648  
CSA C22.2, class 6225-01 File 265615

### Link to the reference

RM CC are modular DIN rail-mounted fuse holders for UL Class CC fuses. They are available with and without LED indication in 1, 2, and 3-pole versions. RM CC fuse holders are IP20 protected from touch by fingers and provide safe breaking and isolation of electrical circuits up to 30 A at 600 V.

### Certificates and Declaration

Conformity to standard #1	UL 428-4 Guide IZLT File E307648
Conformity to standard #2	CSA-C22.2 No. 4248-07, Class 6225-01, File 265615
Conformity to standard #4	ML E307648
Proposition 65 California	WARNING This product can expose you to chemicals including Styrene, which is known to the State of California to cause cancer. For more information go to: <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

### Standards

Conformity to standards	UL
-------------------------	----

### Certificates and Declaration - Safety

UL file number	E307648
----------------	---------

### Technical Characteristics

Length of the product unit [mm]	78
Width of the product unit [mm]	58
Depth of the product unit [mm]	52.5
Weight [kg]	0.17
Fuse melting indicator	Yes
Fuse size	10x38 CC
Number of poles	3
Rated current [A]	30
Size	RM32

### Technical Characteristics - Connection terminals

Max. connection section / AWG	1x- 8awg, 2x-8 AWG (Solid), 10 AWG (Stranded)
Min. connection section / AWG	18AWG

### Technical Characteristics - Environmental

Operating temperature	-4 ... +122°F / -20 ... +50°C
Storage temperature	-40 ... +158°F / -40 ... +70°C

### Technical Characteristics - Short-circuit capacity

Max fuse rating [A]	30
Operation voltage 2 P - 3/4 P	600V
Short-circuit capacity at 600 VDC / Type of fuse	200
Short circuit rating at 600 VAC [kA]	200
Type of fuse	CC
UL General use rating [A]	200

### ETIM - Electrical characteristics

Nominal voltage [V]	600
Number of poles	3
Concurrently switching neutral conductor	No

### ETIM - Mechanical characteristics

Mounting method	DIN rail
For fuse size	Other
Width in number of modular spacings	3
Built-in depth [mm]	40
Degree of protection (IP)	IP2X
<b>ETIM - Technical features</b>	
Lockable	Yes
With optical defect indication	Yes
<b>Logistics</b>	
GTIN/EAN	3596032968359
Customs number	8536105090
Price unit	PC
Weight of the packing unit [kg]	0.17
Length of the packing unit [m]	0.055
Width of the packing unit [m]	0.065
Depth of the packing unit [m]	0.08
<b>Product Details</b>	
Effective date	2016-08-03
Offer Life Cycle Code	40
Country of origin	ES
<b>Classification</b>	
UNSPSC	39121624
ETIM Class	EC002705
IGCC	4974