

87P11011

Strong points

- High-performance power switching in a compact frame
- Safe & reliable operation
- Designed for harsh environments
- Easy to install
- Modular solution for flexible configuration

General characteristics

High switching capacity of 750 VDC per pole with optimum arc containment and significant power loss reduction
 Configurable mechanism (centered or left aligned) to accommodate installation requirements
 Easy auxiliary contacts' integration without the need of any tools
 Used of high temperature withstand materials, No derating up to 131° F / 55° C

Compliance with standards

UL 98B Guide WHVA File E346418
 IEC 60947-3, DC-21B & DC-PV2
 CCC

Link to the reference

INOSYS LBS are multi-polar disconnect switches operated manually using the handle to disconnect DC/PV/ESS circuits safely. They make and break under load conditions, provide safety isolation for low voltage circuits up to 1500 VDC (also available up to 2000kVA), and are suitable for emergency switching. They are available for DC-PV2 utilization category.

Certificates and Declaration

Conformity to standard #1	UL98B
Conformity to standard #2	IEC 60947-3
Proposition 65 California	WARNING This product can expose you to chemicals including Styrene, which is known to the State of California to cause cancer. For more information go to: www.P65Warnings.ca.gov

Environmental Sustainability

PEP Filename	SOCO-00067-V01.02-EN.pdf
Climate change - Total - Cradle to Grave [kg CO ₂ eq.]	59
Climate change - Total - Cradle to Gate [kg CO ₂ eq.]	17

Certificates and Declaration - Safety

UL file number	E346418
----------------	---------

Technical Characteristics

Control operator	Direct : E2 / External : S2
Number of poles	1+1
Rated voltage	1500
Rated current [A]	100
Type	Frontal operation
Frame size	F2

Technical Characteristics - Connection terminals

Max. connection section / AWG	2x2/0
Min. connection section / AWG	2x#12

Technical Characteristics - Environmental

Operating temperature	-4 ... +122°F / -20 ... +50°C
Storage temperature	-40 ... +158°F / -40 ... +70°C

Technical Characteristics - Mechanical

Endurance (number of operating cycles)	10000
--	-------

Technical Characteristics - Short-circuit capacity

Operation voltage 2 P - 3/4 P	1500VDC
Short-circuit capacity at 1000 & 1500 VDC / Prospective short-circuit current [kA rms]	10
UL General use rating [A]	100

ETIM - Electrical characteristics

Number of poles	2
-----------------	---

ETIM - Mechanical characteristics

Suitable for floor mounting	No
Suitable for front mounting 4-hole	Ja
Suitable for front mounting centre	No

Suitable for distribution board installation	Yes
Suitable for intermediate mounting	Yes
Colour control element	Other
Degree of protection (IP), front side	IP20
ETIM - Technical features	
Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	Yes
Version as reversing switch	No
Number of switches	1
Device construction	Built-in device fixed built-in technique
Voltage release optional	No
Type of control element	Other
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection
Logistics	
GTIN/EAN	3596033046735
Customs number	8535301090
Price unit	PC
Weight of the packing unit [kg]	2,46
Length of the packing unit [m]	0,21
Width of the packing unit [m]	0,39
Depth of the packing unit [m]	0,17
Product Details	
Effective date	2018-03-01
Offer Life Cycle Code	40
Country of origin	TN
Classification	
UNSPSC	39122233
ETIM Class	EC000216
IGCC	5290